

## ECK11124



### ADAPTOR WITH INT. AND PORTECTION SP 10A 2P+E 2 PR 10/16A+SCHUKO

Residential > Utility series > Items for domestic use > Adaptors  
> Socket outlet combination > Triple adaptor 10 a - with light  
switch



#### Technical Symbols/Marks/Approvals



#### Norms

CEI 23-50 CEI 23-151

### Description

10A triple system adapter with overload protection and thermal circuit breaker. 10A 2P+E plug type S11. 10/16A 2P+E sockets type P17/11. White color. Made of self-extinguishing V0 technopolymer (UL94 Standard) with high UV resistance. Protected nickel-plated brass pins. Sockets protected against accidental contact. Rated voltage: 250 V~ 50Hz. Abnormal heat resistance (GWT, IEC 60695-2-11 standard): up to 750°C. Protection rating: IP20. Operating temperature: -15°C to +35°C.

**Etim**

**GROUP EG000013 - Domestic switching devices**


**CLASS EC000330 - Socket outlet combination**

<b>Degree of protection (IP)</b>	IP20	<b>RAL-number (similar)</b>	9003	<b>Material</b>	Plastic
<b>Material quality</b>	Thermoplastic	<b>Halogen free</b>	No	<b>Anti-bacterial treatment</b>	No
<b>Surface protection</b>	Untreated	<b>Surface finishing</b>	Glossy	<b>Colour</b>	White
<b>Transparent</b>	No	<b>Impact strength</b>	IK09	<b>Working temperature</b>	-15-35 °C
<b>Compatible with Apple HomeKit</b>	No	<b>Compatible with Google Assistant</b>	No	<b>Compatible with Amazon Alexa</b>	No
<b>IFTTT support available</b>	No	<b>Overvoltage protection</b>	No	<b>With miniature fuse</b>	No
<b>With on/off switch</b>	No	<b>Rotated central insert</b>	No	<b>Nominal current</b>	10 A
<b>Number of socket outlets with protective contact CEE 7/3 (type F)</b>	0	<b>Number of socket outlets British Standard BS 1363</b>	0	<b>Number of socket outlets Italian standard type Bipasso</b>	3
<b>Number of socket outlets Italian standard type P11</b>	0	<b>Number of socket outlets Italian standard type P17</b>	0	<b>Number of socket outlets Italian standard type P30</b>	0
<b>Number of universal multi standard sockets</b>	0	<b>Number of socket outlets Swiss standard type 13</b>	0	<b>Number of socket outlets Swiss standard type 15</b>	0
<b>Number of socket outlets Swiss standard type 23</b>	0	<b>Number of socket outlets Swiss standard type 25</b>	0	<b>Type of mains connection</b>	Italian type P10
<b>NEMA designation</b>	None	<b>Housing shape</b>	Rectangular	<b>Number of socket outlets CEE 7/1 (no protective contact)</b>	0
<b>Number of socket outlets CEE 7/16 (EURO)</b>	0	<b>Number of socket outlets with earth pin</b>	3	<b>Number of cold device socket outlets</b>	0
<b>Number of socket outlets Danish standard (earthing pin, type K)</b>	0	<b>Number of socket outlets with protective contact CEE 7/5 (type E)</b>	0	<b>Number of NEMA-outlets</b>	0
<b>Residual current circuit breaker (RCCB)</b>	No	<b>Mains filter</b>	No	<b>Number of other socket outlets</b>	0
<b>Number of USB connections</b>	0	<b>Overcurrent protection</b>	Yes	<b>Max. connected load</b>	2200 W
<b>With cover</b>	No	<b>Type of plug</b>	Straight	<b>Directly pluggable (without power cord)</b>	Yes

**Barcode**



8032793872917  
**Unit**  
1 NR  
0.1292 [kg]



8057711595273  
**Pack**  
12 NR  
0.165x0.405x0.145 [m]  
1.5504 [kg]



8033576778587  
**Cardboard**  
48 NR  
0.315x0.43x0.34 [m]  
6.2016 [kg]