

ECK11124



**ADAPTOR WITH INT. AND
PORTECTION SP 10A 2P+E 2 PR
10/16A+SCHUKO**

Residential > Utility series > Items for domestic use > Adaptors
> Socket outlet combination > Triple adaptor 10 a - with light
switch



Technical Symbols/Marks/Approvals



Norms

CEI 23-50 CEI 23-151

Etim

GROUP EG000013 - Domestic switching devices


CLASS EC000330 - Socket outlet combination

Degree of protection (IP)	IP20	RAL-number (similar)	9003	Material	Plastic
Material quality	Thermoplastic	Halogen free	No	Anti-bacterial treatment	No
Surface protection	Untreated	Surface finishing	Glossy	Colour	White
Transparent	No	Impact strength	IK09	Working temperature	-15-35 °C
Compatible with Apple HomeKit	No	Compatible with Google Assistant	No	Compatible with Amazon Alexa	No
IFTTT support available	No	Overvoltage protection	No	With miniature fuse	No
With on/off switch	No	Rotated central insert	No	Nominal current	10 A
Number of socket outlets with protective contact CEE 7/3 (type F)	0	Number of socket outlets British Standard BS 1363	0	Number of socket outlets Italian standard type Bipasso	3
Number of socket outlets Italian standard type P11	0	Number of socket outlets Italian standard type P17	0	Number of socket outlets Italian standard type P30	0
Number of universal multi standard sockets	0	Number of socket outlets Swiss standard type 13	0	Number of socket outlets Swiss standard type 15	0
Number of socket outlets Swiss standard type 23	0	Number of socket outlets Swiss standard type 25	0	Type of mains connection	Italian type P10
NEMA designation	None	Housing shape	Rectangular	Number of socket outlets CEE 7/1 (no protective contact)	0
Number of socket outlets CEE 7/16 (EURO)	0	Number of socket outlets with earth pin	3	Number of cold device socket outlets	0
Number of socket outlets Danish standard (earthing pin, type K)	0	Number of socket outlets with protective contact CEE 7/5 (type E)	0	Number of NEMA-outlets	0
Residual current circuit breaker (RCCB)	No	Mains filter	No	Number of other socket outlets	0
Number of USB connections	0	Overcurrent protection	Yes	Max. connected load	2200 W
With cover	No	Type of plug	Straight	Directly pluggable (without power cord)	Yes

Barcode



8032793872917
Unit
1 NR
0.1292 [kg]



8057711595273
Pack
12 NR
0.165x0.405x0.145 [m]
1.5504 [kg]



8033576778587
Cardboard
48 NR
0.315x0.43x0.34 [m]
6.2016 [kg]