



ECK11125

Residential > Utility series > Items for domestic use > Adaptors
> Socket outlet combination > Triple adaptor + usb socket



Technical Symbols/Marks/Approvals



Norms

CEI 23-50 CEI 23-151

Description

16A triple system adapter. With automatic (less than 10 lm) or manual night light. Equipped with two USB ports (2400 mA total, 1200 mA x 2) and a smartphone holder. 16A 2P+E plug, type S17. 10/16A 2P+E sockets type P17/11 + 10/16A Schuko/dual-standard socket type P17/11-30. White color. Made of self-extinguishing V0 technopolymer (UL94 Standard) with high UV resistance. Protected nickel-plated brass pins. Sockets protected against accidental contact. Rated voltage: 250 V~ 50Hz. Abnormal heat resistance (GWT, IEC 60695-2-11 standard): up to 750°C. Protection rating: IP20. Operating temperature: -15°C to +35°C.

Etim

GROUP EG000013 - Domestic switching devices

CLASS EC000330 - Socket outlet combination

Degree of protection (IP)	IP20	RAL-number (similar)	9003	Material	Plastic
Material quality	Thermoplastic	Halogen free	No	Anti-bacterial treatment	No
Surface protection	Untreated	Surface finishing	Glossy	Colour	White
Transparent	No	Impact strength	IK09	Working temperature	-15-35 °C
Compatible with Apple HomeKit	No	Compatible with Google Assistant	No	Compatible with Amazon Alexa	No
IFTTT support available	No	Overvoltage protection	No	With miniature fuse	No
With on/off switch	Yes	Rotated central insert	No	Nominal current	16 A
Number of socket outlets with protective contact CEE 7/3 (type F)	1	Number of socket outlets British Standard BS 1363	0	Number of socket outlets Italian standard type Bipasso	3
Number of socket outlets Italian standard type P11	0	Number of socket outlets Italian standard type P17	0	Number of socket outlets Italian standard type P30	0
Number of universal multi standard sockets	0	Number of socket outlets Swiss standard type 13	0	Number of socket outlets Swiss standard type 15	0
Number of socket outlets Swiss standard type 23	0	Number of socket outlets Swiss standard type 25	0	Type of mains connection	Italian type P17
NEMA designation	None	Housing shape	Rectangular	Number of socket outlets CEE 7/1 (no protective contact)	0
Number of socket outlets CEE 7/16 (EURO)	0	Number of socket outlets with earth pin	3	Number of cold device socket outlets	0
Number of socket outlets Danish standard (earthing pin, type K)	0	Number of socket outlets with protective contact CEE 7/5 (type E)	0	Number of NEMA-outlets	0
Residual current circuit breaker (RCCB)	No	Mains filter	No	Number of other socket outlets	0
Number of USB connections	2	Overcurrent protection	No	Max. connected load	3500 W
With cover	No	Type of plug	Straight	Directly pluggable (without power cord)	Yes

Barcode



8056351665230
Unit
1 NR
0.23 [kg]



8056351665247
Pack
12 NR
0.2x0.69x0.13 [m]
2.76 [kg]



8056351665254
Cardboard
48 NR
0.41x0.71x0.28 [m]
11.04 [kg]