

# ECK11156

## MULTIPLE SOCKET WHITE 6 GANGS

Residential > Utility series > Items for domestic use > Multiple socket bases > Multiple sockets > Multiple socket base with cable

### Technical Symbols/Marks/Approvals

IP20 | UL94 V0 | GWT 750° | CE | RoHS II | MADE IN PRC

### Norms

CEI 23-50 CEI 23-124

## Description

6-socket dual-standard power strip with cable and plug. 6 sockets 2P+E 10/16A type P17/11. Made of self-extinguishing V0 technopolymer (UL94 Standard) with high UV resistance. White color. Sockets protected against accidental contact. 2P+E 16A plug type S17 molded to the cable with protected nickel-plated brass pins. H05VV-F 3G1 cable - double insulation - VDE - length 1.5 m. Rated voltage: 250 V~. Maximum power: 3,500 W. Abnormal heat resistance (GWT, IEC 60695-2-11 standard): up to 750°C. Protection rating: IP20. Operating temperature: -15°C to +35°C.



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

## Etim

### GROUP EG000013 - Domestic switching devices

### CLASS EC000330 - Socket outlet combination

| | | | | | |
|---|---|---|---|---|---|
| **Degree of protection (IP)** | IP20 | **RAL-number (similar)** | 9003 | **Material** | Plastic |
| **Material quality** | Thermoplastic | **Halogen free** | No | **Anti-bacterial treatment** | No |
| **Surface protection** | Untreated | **Surface finishing** | Glossy | **Colour** | White |
| **Transparent** | No | **Impact strength** | IK09 | **Working temperature** | -15-35 °C |
| **Compatible with Apple HomeKit** | No | **Compatible with Google Assistant** | No | **Compatible with Amazon Alexa** | No |
| **IFTTT support available** | No | **Overvoltage protection** | No | **With miniature fuse** | No |
| **With on/off switch** | No | **Rotated central insert** | No | **Nominal current** | 16 A |
| **Core cross section** | 1 mm² | **Number of socket outlets with protective contact CEE 7/3 (type F)** | 0 | **Number of socket outlets British Standard BS 1363** | 0 |
| **Number of socket outlets Italian standard type Bipasso** | 6 | **Number of socket outlets Italian standard type P11** | 0 | **Number of socket outlets Italian standard type P17** | 0 |
| **Number of socket outlets Italian standard type P30** | 0 | **Number of universal multi standard sockets** | 0 | **Number of socket outlets Swiss standard type 13** | 0 |
| **Number of socket outlets Swiss standard type 15** | 0 | **Number of socket outlets Swiss standard type 23** | 0 | **Number of socket outlets Swiss standard type 25** | 0 |
| **Type of mains connection** | Italian type P17 | **NEMA designation** | None | **Housing shape** | Rectangular |
| **Number of socket outlets CEE 7/1 (no protective contact)** | 0 | **Number of socket outlets CEE 7/16 (EURO)** | 0 | **Number of socket outlets with earth pin** | 6 |
| **Number of cold device socket outlets** | 0 | **Number of socket outlets Danish standard (earthing pin, type K)** | 0 | **Number of socket outlets with protective contact CEE 7/5 (type E)** | 0 |
| **Number of NEMA-outlets** | 0 | **Residual current circuit breaker (RCCB)** | No | **Mains filter** | No |
| **Number of other socket outlets** | 0 | **Number of USB connections** | 0 | **Overcurrent protection** | No |
| **Max. connected load** | 3500 W | **With cover** | No | **Length of power cord** | 1.5 m |
| **Type of plug** | Straight | **Directly pluggable (without power cord)** | No | | |

## Barcode

8033576775005

**Unit**

1 NR

0.2875 [kg]

8059307219662

**Cardboard**

40 NR

0.255x0.445x0.24 [m]

11.5 [kg]



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.