

**ECK22101**

**CABLE REEL 2 SCHUKO/ITALIAN - 5 m**

Residential > Utility series > Items for domestic use > Cable reels > Cable reel > Compact cable reels



**Technical Symbols/Marks/Approvals**



**Norms**

IEC 60884-1 IEC 60884-2-5 EN 61242

**Description**

Domestic cable reel with 2 Schuko/dual-standard 2P+E 10/16A sockets, type P17/11-30. Made of self-extinguishing V0 technopolymer (UL94 standard) with high UV resistance. Blue/orange color. Sockets with shuttered outlets for protection against accidental contact. 16A type S17 plug permanently molded to the cable with protected nickel-plated brass pins. H05VV-F 3G1.5 PVC cable. Length: 5 m. Resettable thermal cutout with intervention at cable temperature >55°C. Rated voltage: 250 V~ 50Hz. Maximum power: 3000 W. For powering Class I or II appliances. Abnormal heat resistance (GWT standard IEC 60695-2-11): up to 750°C. Protection rating: IP20. Operating temperature: -15°C to +35°C.

**Etim**

**GROUP EG020002 - Accessories for power tools**

**CLASS EC000191 - Cable reel**

Degree of protection (IP)	IP20	Colour	Blue	Housing material	Plastic
Number of cores	3	Cable assembly	H05VV-F	Core cross section	1.5 mm²
Number of CEE socket outlets (IEC 60309)	0	Number of socket outlets with protective contact CEE 7/3 (type F)	2	Number of socket outlets British Standard BS 1363	0
Number of socket outlets British standard	0	Number of socket outlets Italian standard type Bipasso	2	Number of socket outlets Italian standard type P11	0
Number of socket outlets Italian standard type P17	0	Number of socket outlets Italian standard type P30	0	Number of universal multi standard sockets	0
Number of socket outlets Swiss standard type 13	0	Number of socket outlets Swiss standard type 15	0	Number of socket outlets Swiss standard type 23	0
Number of socket outlets Swiss standard type 25	0	Type of mains connection	Italian type P17	Cable length	5 m
With mounting frame	Yes	Automatic cable winding	No	With thermal overload protection	Yes
With locking	No	With lamp	No	With charging cable for E-Mobility	No
Earthing cable reel	No	Protection	Overcurrent switch		

## Technical Characteristics

<b>Power cable coiled</b>	1.1 kW	<b>Power cable unwound</b>	3.0 kW	<b>Installed sockets 10/16A 2P+E</b>	2
<b>16A plug</b>	S17 - 2P+T				

## Barcode



8033576775470

**Unit**

1 NR

0.95 [kg]



8059307219723

**Cardboard**

10 NR

0.35x0.39x0.25 [m]

9.5 [kg]