elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECK22101

CABLE REEL 2 SCHUKO/ITALIAN - 5 m

Residential > Utility series > Items for domestic use > Cable reels > Cable reel > Compact cable reels

Technical Symbols/Marks/Approvals

IP20 | UL94 V0 | GWT 750° | CE | RoHS II | MADE IN PRC

Norms

IEC 60884-1 IEC 60884-2-5 EN 61242

Description

Domestic cable reel with 2 Schuko/dual-standard 2P+E 10/16A sockets, type P17/11-30. Made of self-extinguishing V0 technopolymer (UL94 standard) with high UV resistance. Blue/orange color. Sockets with shuttered outlets for protection against accidental contact. 16A type S17 plug permanently molded to the cable with protected nickel-plated brass pins. H05VV-F 3G1.5 PVC cable. Length: 5 m. Resettable thermal cutout with intervention at cable temperature >55°C. Rated voltage: 250 V~ 50Hz. Maximum power: 3000 W. For powering Class I or II appliances. Abnormal heat resistance (GWT standard IEC 60695-2-11): up to 750°C. Protection rating: IP20. Operating temperature: -15°C to +35°C.

Etim

GROUP EG020002 - Accessories for power tools

CLASS EC000191 - Cable reel

Degree of protection (IP)	IP20	**Colour**	Blue	**Housing material**	Plastic
Number of cores	3	**Cable assembly**	H05VV-F	**Core cross section**	1.5 mm²
Number of CEE socket outlets (IEC 60309)	0	**Number of socket outlets with protective contact CEE 7/3 (type F)**	2	**Number of socket outlets British Standard BS 1363**	0
Number of socket outlets British standard	0	**Number of socket outlets Italian standard type Bipasso**	2	**Number of socket outlets Italian standard type P11**	0
Number of socket outlets Italian standard type P17	0	**Number of socket outlets Italian standard type P30**	0	**Number of universal multi standard sockets**	0
Number of socket outlets Swiss standard type 13	0	**Number of socket outlets Swiss standard type 15**	0	**Number of socket outlets Swiss standard type 23**	0
Number of socket outlets Swiss standard type 25	0	**Type of mains connection**	Italian type P17	**Cable length**	5 m
With mounting frame	Yes	**Automatic cable winding**	No	**With thermal overload protection**	Yes
With locking	No	**With lamp**	No	**With charging cable for E-Mobility**	No
Earthing cable reel	No	**Protection**	Overcurrent switch		

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Technical Characteristics

Power cable coiled	1.1 kW	**Power cable unwound**	3.0 kW	**Installed sockets 10/16A 2P+E**	2
16A plug	S17 - 2P+T				

Barcode

8033576775470

Unit

1 NR

0.95 [kg]

8059307219723

Cardboard

10 NR

0.35x0.39x0.25 [m]

9.5 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.