

ECK22103

CABLE REEL 4 SCHUKO/ITALIAN - 20 m

Residential > Utility series > Items for domestic use > Cable reels > Cable reel > Compact cable reels

Technical Symbols/Marks/Approvals

IP20 | UL94 V0 | GWT 750° | CE | RoHS II | MADE IN PRC

Norms

IEC 60884-1 IEC 60884-2-5 EN 61242

Description

Domestic cable reel with 4 Schuko/dual-standard 2P+E 10/16A sockets, type P17/11-30. Made of self-extinguishing V0 technopolymer (UL94 standard) with high UV resistance. Blue/orange color. Sockets with shuttered outlets for protection against accidental contact. 16A type S17 plug permanently molded to the cable with protected nickel-plated brass pins. H05VV-F 3G1.5 PVC cable. Length: 20 m. Resettable thermal cutout with intervention at cable temperature >55°C. Rated voltage: 250 V~ 50Hz. Maximum power: 3000 W. For powering Class I or II appliances. Abnormal heat resistance (GWT standard IEC 60695-2-11): up to 750°C. Protection rating: IP20. Operating temperature: -15°C to +35°C.

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Etim

GROUP EG020002 - Accessories for power tools

CLASS EC000191 - Cable reel

Degree of protection (IP)	IP20	**Colour**	Blue	**Housing material**	Plastic
Number of cores	3	**Cable assembly**	H05VV-F	**Core cross section**	1.5 mm²
Number of CEE socket outlets (IEC 60309)	0	**Number of socket outlets with protective contact CEE 7/3 (type F)**	4	**Number of socket outlets British Standard BS 1363**	0
Number of socket outlets British standard	0	**Number of socket outlets Italian standard type Bipasso**	4	**Number of socket outlets Italian standard type P11**	0
Number of socket outlets Italian standard type P17	0	**Number of socket outlets Italian standard type P30**	0	**Number of universal multi standard sockets**	0
Number of socket outlets Swiss standard type 13	0	**Number of socket outlets Swiss standard type 15**	0	**Number of socket outlets Swiss standard type 23**	0
Number of socket outlets Swiss standard type 25	0	**Type of mains connection**	Italian type P17	**Cable length**	20 m
With mounting frame	Yes	**Automatic cable winding**	No	**With thermal overload protection**	Yes
With locking	No	**With lamp**	No	**With charging cable for E-Mobility**	No
Earthing cable reel	No	**Protection**	Overcurrent switch		

Technical Characteristics

Power cable coiled	1.1 kW	**Power cable unwound**	3.0 kW	**Installed sockets 10/16A 2P+E**	4
16A plug	S17 - 2P+T				

Barcode

8033576775494

Unit

1 NR

3.0667 [kg]

8059307219747

Cardboard

6 NR

0.405x0.48x0.305 [m]

18.4002 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.