



## ECK22105

### CABLE REEL 4 SCHUKO/ITALIAN - 25 m METALLIC SUPPORT



Residential > Utility series > Items for domestic use > Cable reels > Cable reel > Cable reels with kickstand

#### Technical Symbols/Marks/Approvals



#### Norms

IEC 60884-1 IEC 60884-2-5 EN 61242

## Description

Domestic cable reel with 4 Schuko/dual-standard 2P+E 10/16A sockets, type P17/11-30. Made of self-extinguishing V0 technopolymer (UL94 standard) with high UV resistance. Black color. On a metal stand with a soft-grip carrying handle. 240 mm diameter drum with winding handle. Sockets with shuttered outlets for protection against accidental contact. 16A type S17 plug permanently molded to the cable with protected nickel-plated brass pins. H05VV-F 3G1.5 PVC cable. Length: 25 m. Resettable thermal cutout with intervention at cable temperature >55°C. Rated voltage: 250 V~ 50Hz. Maximum power: 3000 W. For powering Class I or II appliances. Abnormal heat resistance (GWT standard IEC 60695-2-11): up to 750°C. Protection rating: IP20. Operating temperature: -15°C to +35°C.

**Etim**

**GROUP EG020002 - Accessories for power tools**

**CLASS EC000191 - Cable reel**

<b>Degree of protection (IP)</b>	IP20	<b>Colour</b>	Black	<b>Housing material</b>	Plastic
<b>Number of cores</b>	3	<b>Cable assembly</b>	H05VV-F	<b>Core cross section</b>	1.5 mm <sup>2</sup>
<b>Number of CEE socket outlets (IEC 60309)</b>	0	<b>Number of socket outlets with protective contact CEE 7/3 (type F)</b>	4	<b>Number of socket outlets British Standard BS 1363</b>	0
<b>Number of socket outlets British standard</b>	0	<b>Number of socket outlets Italian standard type Bipasso</b>	4	<b>Number of socket outlets Italian standard type P11</b>	0
<b>Number of socket outlets Italian standard type P17</b>	0	<b>Number of socket outlets Italian standard type P30</b>	0	<b>Number of universal multi standard sockets</b>	0
<b>Number of socket outlets Swiss standard type 13</b>	0	<b>Number of socket outlets Swiss standard type 15</b>	0	<b>Number of socket outlets Swiss standard type 23</b>	0
<b>Number of socket outlets Swiss standard type 25</b>	0	<b>Type of mains connection</b>	Italian type P17	<b>Cable length</b>	25 m
<b>With mounting frame</b>	Yes	<b>Automatic cable winding</b>	No	<b>With thermal overload protection</b>	Yes
<b>With locking</b>	No	<b>With lamp</b>	No	<b>With charging cable for E-Mobility</b>	No
<b>Earthing cable reel</b>	No	<b>Protection</b>	Overcurrent switch		

**Technical Characteristics**

<b>Power cable coiled</b>	1.1 kW	<b>Power cable unwound</b>	3.0 kW	<b>Installed sockets 10/16A 2P+E</b>	4
<b>16A plug</b>	S17 - 2P+T				

**Barcode**



8033954879059  
**Unit**  
1 NR  
4 [kg]



8059307219761  
**Cardboard**  
2 NR  
0.26x0.365x0.355 [m]  
8 [kg]