











## **Technical Symbols/Marks/Approvals**

IP <b>20</b>	<u>UL94</u> <b>V0</b>	GWT <b>750</b> °	CE	RoHS II	Z	MADE IN PRC
	• •	100				

#### **Norms**

CEI 23-50 CEI 23-124

## **Etim**

# GROUP EG000053 - Batteries, chargers and power cords

### CLASS EC001576 - Power cord

Degree of protection (IP)		Length	3 m	Material outer sheath Polyvinyl chloride (	PVC)
Colour outer sheath	White	Reaction-to-fire according to EN 13501-6: Class	Eca	Reaction-to-fire according to EN 13501-6: Smoke production	None
Reaction-to-fire according to EN 13501-6: Flaming droplets/particles	None	Reaction-to-fire according to EN 13501-6: Acidity	None	Outer diameter approximate 6.	3 mm
Nominal voltage	300-500 V	Frequency	50-60 Hz	Number of cores	3
Nominal cross section conductor	0.75 mm	Nominal current	10 A	Temperature resistance -15-	35 °C
With protective conductor	Yes	Oil resistant according to EN IEC 60811-404	No	Connection 1	Other
Connection 2	Other	Cable entry connection 2	Straight	System-oriented connector system	No
Spiralized cable	No	With cord switch	No		





## **Barcode**



8033576775395

Unit

1 NR

0.276 [kg]



8059307219785

Cardboard

50 NR

0.255x0.435x0.24 [m]

13.8 [kg]