

ECK22203



CABLE EXTENSION WHITE 3 m

Residential > Utility series > Items for domestic use > Extension cords > Power cord > Linear extension cords



IMMAGINE RAPPRESENTATIVA **EC** REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals



Norms

CEI 23-50 CEI 23-124

Description

Extension cable with 2P+E 16A dual-standard plug and socket, type S17/P17/11. Plug and socket made of self-extinguishing V0 technopolymer (UL94 standard) with high UV resistance. White color. Socket with shuttered outlets for protection against accidental contact. Plug permanently molded to the cable with protected nickel-plated brass pins. H05VV-F 3G1.5 cable - double insulation - VDE. Length: 3 m. Rated voltage: 250 V~ 50Hz. Maximum power: 3500W. Abnormal heat resistance (GWT standard IEC 60695-2-11): up to 750°C. Protection rating: IP20. Operating temperature: -15°C to +35°C.

Etim

GROUP EG000053 - Batteries, chargers and power cords

CLASS EC001576 - Power cord

Degree of protection (IP)	IP20	Length	3 m	Material outer sheath	Polyvinyl chloride (PVC)
Colour outer sheath	White	Reaction-to-fire according to EN 13501-6: Class	Eca	Reaction-to-fire according to EN 13501-6: Smoke production	None
Reaction-to-fire according to EN 13501-6: Flaming droplets/particles	None	Reaction-to-fire according to EN 13501-6: Acidity	None	Outer diameter approximate	8 mm
Nominal voltage	300-500 V	Frequency	50-60 Hz	Number of cores	3
Nominal cross section conductor	1.5 mm ²	Nominal current	16 A	Temperature resistance	-15-35 °C
With protective conductor	Yes	Oil resistant according to EN IEC 60811-404	No	Connection 1	Other
Cable entry connection 1	Straight	Connection 2	Other	Cable entry connection 2	Straight
System-oriented connector system	No	Spiralized cable	No	With cord switch	No

Barcode



8033576775432

Unit

1 NR

4 [kg]



8059307219808

Cardboard

50 NR

0.26x0.46x0.295 [m]

200 [kg]