

ECK33416

SOCKET BLACK BI-POWER SCHUKO 10/16A

Residential > Utility series > Items for domestic use > Plugs and sockets > Socket with earthing > Mobile socket - schuko



Technical Symbols/Marks/Approvals

IP20	UL94 V0	GWT 750°	CE	RoHS II		MADE IN PRC
------	------------	-------------	----	---------	--	-------------------

Norms

CEI 23-50

Description

10/16A 2P+E dual-standard Schuko rewirable socket, type P17-11-P30. Black color. Made of self-extinguishing V0 technopolymer (UL94 standard) with high UV resistance. Shuttered outlets for protection against accidental contact. Protective cable sleeve and cord grip with screws. Rated voltage: 250 V~ 50Hz. Abnormal heat resistance (GWT standard IEC 60695-2-11): up to 750°C. Protection rating: IP20. Operating temperature: -15°C to +35°C.

Etim

GROUP EG000013 - Domestic switching devices

CLASS EC001327 - Coupler with protective contact

Number of poles	3	Degree of protection (IP)	IP20	Material	Plastic
Material quality	Thermoplastic	Halogen free	Yes	Colour	Black
Model	Coupler CEE 7/3 (Typ F)	RAL-number	9005	Nominal voltage	250 V
Nominal current	16 A	For heavy conditions according to VDE	No	Connection system	Screwed terminal
Insert direction	Straight	With voltage indication	No	With quick-lock	No

Barcode



8054320289616

Pack

20 NR

21.14 [kg]



8057711595525

Cardboard

200 NR

0.305x0.545x0.245 [m]

211.4 [kg]