

EC20010



**3-MODULE TOWER ADAPTOR BOX
83,5 mm HOLE C.E DISTANCE-WHITE
RAL 9001**



Trunkings > Wall and ceiling > Skirting and wall trunkings > Series 20 - trunking fittings > Modular boxes for wiring devices

Technical Symbols/Marks/Approvals



Norms

EN 50085-1 EN 50085-2-1

Description

The 83.5 mm center-to-center - 3-module appliance box can be used for installing up to 3 Italian standard appliances. With a blank cover, it can be used as a junction box. The item is composed of four assembled parts: the lower part, which snaps onto the trunking and the wall with 4 screws, serves as an insulating base and a grid separating the various circuits. The upper part is shaped to accommodate the appliance mounting frames. The trunking cover, in addition to providing protection, gives the whole a harmonious and elegant shape. The integrated end cap allows the trunking to be interrupted without the need for an additional end cap.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling
CLASS EC000079 - Appliance box for skirting duct

| | | | | | |
|-----------------------------------|-------|--|------------|------------------------------|----------|
| Degree of protection (IP) | IP40 | Mounting direction | Horizontal | Material | Plastic |
| Halogen free | Yes | Anti-bacterial treatment | No | Colour | White |
| Impact strength | IK08 | RAL-number | 9001 | Working temperature | -5-60 °C |
| Decoration | None | Mounting method installation unit | Standard | Height baseboard duct | 70 mm |
| Depth plinth skirting duct | 20 mm | Number of device units | 3 | Equipped with | None |

Technical Characteristics

dimensions 140 x 185 x 50 mm

Documentation available for download



Certification
Battiscopa Serie
20.pdf



General data sheets
SCI_20 BATT.pdf

Barcode



8033576770253
Unit
1 NR
0.24 [kg]



8059307212526
Cardboard
10 NR
0.39x0.295x0.15 [m]
2.4 [kg]