

ECK33504

ADAPTOR SING WHITE 10A

Residential > Utility series > Items for domestic use > Adaptors > Plug adapter > Single schuko adaptor



IMMAGINE RAPPRESENTATIVA **EC** REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals

IP20	UL94 V0	GWT 750°	CE		MADE IN PRC
------	------------	-------------	----	--	-------------

Norms

CEI 23-50 CEI 23-57

Description

10A system adapter. 10A 2P+E plug type S11. 16A P30 Schuko socket. White color. Made of self-extinguishing V0 technopolymer (UL94 Standard) with high UV resistance. Protected nickel-plated brass pins. Sockets protected against accidental contact. Rated voltage: 250 V~ 50Hz. Abnormal heat resistance (GWT, IEC 60695-2-11 standard): up to 750°C. Protection rating: IP20. Operating temperature: -15°C to +35°C.

Etim

GROUP EG000013 - Domestic switching devices

CLASS EC001513 - Plug adapter

Colour	White	Model	Single	Nominal voltage	200-250 V
With plug for AU/NZ/PG/AR (AS/NZS 3112) (type I)	No	With plug for BE/DE/NL/RU (protective contact CEE 7/4, type F)	No	With plug for BE/DE/NL/RU/CH (Euro) (type C)	No
With plug for CH (SEV 1011 type 11) (type J)	No	With plug for CH (SEV 1011 type 12) (type J)	No	With plug for CH (SEV 1011 type 23) (type J)	No
With plug for FR (earth pin) (type E)	No	With plug for UK/HK (BS 1363) (type G)	No	With plug for IT (S/P 11)	Yes
With plug for IT (S/P 17) (type L)	No	With plug for US/CA/CN (NEMA 1-15) (type A)	No	With plug for US/CA/CN (NEMA 5-15) (type B)	No
Type of bus	IT (P 30)	Number of USB ports	0	Nominal current	10-10 A

Barcode



8054320289531

Pack

20 NR

0.8 [kg]



8057711595600

Cardboard

200 NR

0.25x0.455x0.24 [m]

8 [kg]