



ECK51019

PORTABLE LED PROJECTOR IP65 100W WITH SUPPORT



Residential > Utility series > Lighting > Floodlights > Floodlights
for construction site > Floodlights for construction site

Technical Symbols/Marks/Approvals



Description

LED floodlight made of black-painted die-cast aluminum. Adjustable tripod stand (950-1800 mm) made of yellow-painted steel. Smooth aluminum reflector. Rated voltage: 240V~. LED module power: 100 W. Color temperature: cold white light. Brightness: 9000 lm. Type S31 Schuko plug. H05RN-F 3G1 VDE cable. Length: 1.5 m. Protection rating: IP65.

Etim

GROUP EG000027 - Luminaires

CLASS EC000346 - Building site lighting luminaire

Degree of protection (IP)	IP65	Impact strength	IK09	Width	270 mm
Height	200 mm	Depth	43 mm	Nominal voltage	220-240 V
Connection type	Other	With light source	Yes	Housing material	Aluminium
Protection class according to IEC 61140	II	Lamp holder	None	Lamp type	LED not exchangeable
Housing colour	Black	Colour of light	White	With socket outlet	No
Energy efficiency class of the light source according to EU regulation 2019/2015	A	With wheels	No	With stand holder	Yes
With stand	Yes	Colour of stand	Yellow	With protective cover	No
Rated lifetime L70/B50 at 25 °C	20000 h	Suitable for lamp power	100-100 W	Rated luminous flux according to IEC 62722-2-1	9000 lm
Colour temperature	6500-6500 K	Type of wiring	Ending	Conductor cross section	1 mm²
Connection cable length	2.5 m				

Barcode



8032793878438

Unit

1 NR

3.9 [kg]



8032793878452

Cardboard

2 NR

0.23x0.64x0.275 [m]

7.8 [kg]