

## ECMA12575

### MINITRUNKING HINGED LID AND SELF-ADHES. BOTTOM 12.5X7.5



Trunkings > Wall and ceiling > Miniature solid trunkings >  
Series ma - adhesive taped and hinged lid > Mini/maxi  
trunkings > White



IMMAGINE  
RAPPRESENTATIVA

EC

REPRESENTATIVE  
IMAGE

#### Technical Symbols/Marks/Approvals

|      |      |            |             |    |         |                     |
|------|------|------------|-------------|----|---------|---------------------|
| IK04 | IP40 | UL94<br>V0 | GWT<br>960° | CE | RoHS II | MADE<br>IN<br>ITALY |
|------|------|------------|-------------|----|---------|---------------------|

#### Norms

EN 50085-1 EN 50085-2-1

## Description

Mini-trunking made of self-extinguishing rigid PVC technopolymer. With adhesive strip for permanent attachment. Integrated lid with snap closure.

## Etim

**GROUP EG000006 - Installation ducts for wall and ceiling**

**CLASS EC000059 - Mini/maxi trunking**

|                                       |               |                                       |                    |                                     |                          |
|---------------------------------------|---------------|---------------------------------------|--------------------|-------------------------------------|--------------------------|
| <b>Degree of protection (IP)</b>      | IP40          | <b>Material</b>                       | Plastic            | <b>Material quality</b>             | Polyvinyl chloride (PVC) |
| <b>Halogen free</b>                   | No            | <b>Anti-bacterial treatment</b>       | No                 | <b>Surface protection</b>           | Untreated                |
| <b>Colour</b>                         | White         | <b>Transparent</b>                    | No                 | <b>Impact strength</b>              | IK04                     |
| <b>Type of fastening</b>              | Self-adhesive | <b>Width</b>                          | 12.5 mm            | <b>Height</b>                       | 7.5 mm                   |
| <b>Length</b>                         | 2 m           | <b>Usable cross section</b>           | 54 mm <sup>2</sup> | <b>RAL-number</b>                   | 9001                     |
| <b>With protective foil</b>           | No            | <b>Working temperature</b>            | -5-60 °C           | <b>Cover model</b>                  | With film hinge          |
| <b>Suitable for circuit integrity</b> | No            | <b>Number of permanent partitions</b> | 0                  | <b>Number of plug-in partitions</b> | 0                        |
| <b>With cable fixing clip</b>         | No            | <b>With duct connector</b>            | No                 | <b>Delivery on roll</b>             | No                       |
| <b>Pre-stamping</b>                   | No            |                                       |                    |                                     |                          |

## Barcode



8054320287841

**Cardboard**

200 MT

0.195x0.102x2.025 [m]

10 [kg]