


ECMC2010B-SAC

MINITRUNKING FRONT-HOOKING LID 20X10 WHITE 1 COMPARTMENT BAGS OF 10 BARS

Trunkings > Wall and ceiling > Miniature solid trunkings > Series mc - front lid > Mini/maxi trunkings > White (10-pack)



Technical Symbols/Marks/Approvals



Norms

EN 50085-1 EN 50085-2-1

Description

Mini-trunking made of self-extinguishing rigid PVC technopolymer. The bottom is pre-drilled for fastening with screws and anchors. The bottom is designed for quick fastening with silicone adhesives. The front-hinged lid is supplied assembled.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000059 - Mini/maxi trunking

Degree of protection (IP)	IP40	Material	Plastic	Material quality	Polyvinyl chloride (PVC)
Halogen free	No	Anti-bacterial treatment	No	Surface protection	Untreated
Colour	White	Transparent	No	Impact strength	IK07
Type of fastening	Bottom perforation	Width	20 mm	Height	10 mm
Length	2 m	Usable cross section	126 mm ²	RAL-number	9001
With protective foil	No	Working temperature	-5-60 °C	Cover model	Loose
Suitable for circuit integrity	No	Number of permanent partitions	0	Number of plug-in partitions	0
With cable fixing clip	No	With duct connector	No	Delivery on roll	No
Pre-stamping	No				

Documentation available for download



Instruction booklet
Istruzioni minicanali.pdf



Certification
Canali e Minic Serie MC-CP.pdf




Certification
LICENCE 669941_CP-MC.pdf

Barcode



8056351667708
Pack
20 MT
2 [kg]



8056351667968
Cardboard
100 MT
10 [kg]