

EC20011

3-MODULE WALL ADAPTOR BOX 83,5 mm HOLE C.E DISTANCE-WHITE RAL 9001



Trunkings > Wall and ceiling > Skirting and wall trunkings > Series 20 - trunking fittings > Modular boxes for wiring devices

Technical Symbols/Marks/Approvals



Norms

EN 50085-1 EN 50085-2-1

Description

The 83.5 mm distance between center lines - 3 modules - wall-mounted device box can be used for the installation of up to 3 Italian standard devices. For installation with a vertical frame profile. The item is composed of four assembled parts: the lower part, which snaps onto the trunking and the wall with 4 screws, which serves as an insulating base and a grid separating the various circuits. The upper part is appropriately shaped to accommodate the device fixing frames. The trunking cover, in addition to having a protective function, gives the whole a harmonious and elegant shape. The integrated end cap allows the trunking to be interrupted without using an additional end cap.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000079 - Appliance box for skirting duct

Degree of protection (IP)	IP40	Mounting direction	Vertical	Material	Plastic
Halogen free	Yes	Anti-bacterial treatment	No	Colour	White
Impact strength	IK08	RAL-number	9001	Working temperature	-5-60 °C
Decoration	None	Mounting method installation unit	Standard	Height baseboard duct	70 mm
Depth plinth skirting duct	20 mm	Number of device units	3	Equipped with	None

Technical Characteristics

dimensions 212 x 112 x 50 mm

Documentation available for download



Certification
Battiscopa Serie
20.pdf



General data sheets
SCI_20 BATT.pdf

Barcode



8033576770277
Unit
1 NR
0.23 [kg]



8059307212557
Cardboard
10 NR
0.39x0.295x0.21 [m]
2.3 [kg]