

ECMC4025M

MINI TRUNKINGS 40X25 BROWN

Trunkings > Wall and ceiling > Miniature solid trunkings > Series mc - front lid > Mini/maxi trunkings > Brown



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals

IK07	IP40	UL94 V0	GWT 960°	CE	RoHS II		MADE IN ITALY
------	------	------------	-------------	----	---------	--	---------------

Norms

EN 50085-1 EN 50085-2-1

Description

Mini-trunking made of self-extinguishing rigid PVC technopolymer. The bottom is pre-drilled for fastening with screws and anchors. The bottom is designed for quick fastening with silicone adhesives. The front-hinged lid is supplied assembled.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000059 - Mini/maxi trunking

Degree of protection (IP)	IP40	Material	Plastic	Material quality	Polyvinyl chloride (PVC)
Halogen free	No	Anti-bacterial treatment	No	Surface protection	Untreated
Colour	Brown	Transparent	No	Impact strength	IK07
Type of fastening	Bottom perforation	Width	40 mm	Height	25 mm
Length	2 m	Usable cross section	752 mm ²	RAL-number	8014
With protective foil	No	Working temperature	-5-60 °C	Cover model	Loose
Suitable for circuit integrity	No	Number of permanent partitions	0	Number of plug-in partitions	0
With cable fixing clip	No	With duct connector	No	Delivery on roll	No
Pre-stamping	No				

Documentation available for download

Instruction booklet
Istruzioni minicanali.pdf

Certification
Canali e Minic Serie MC-CP.pdf

Barcode



8054320287117

Cardboard

80 MT

0.26x0.18x2.027 [m]

21 [kg]