elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECMC5020-2B

MINITRUNKING FRONT-HOOKING LID 50X20 WHITE 3 COMPARTMENTS

Trunkings > Wall and ceiling > Miniature solid trunkings > Series mc - front lid > Mini/maxi trunkings > White

Technical Symbols/Marks/Approvals

IP40 | IK07 | UL94 V0 | GWT 960° | CE | RoHS II | MADE IN ITALY

Norms

EN 50085-1 EN 50085-2-1

Description

Mini-trunking made of self-extinguishing rigid PVC technopolymer. The bottom is pre-drilled for fastening with screws and anchors. The bottom is designed for quick fastening with silicone adhesives. The front-hinged lid is supplied assembled.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000059 - Mini/maxi trunking

Degree of protection (IP)	IP40	**Material**	Plastic	**Material quality**	Polyvinyl chloride (PVC)
Halogen free	No	**Anti-bacterial treatment**	No	**Surface protection**	Untreated
Colour	White	**Transparent**	No	**Impact strength**	IK07
Type of fastening	Bottom perforation	**Width**	50 mm	**Height**	20 mm
Length	2000 mm	**Usable cross section**	615 mm²	**RAL-number**	9001
With protective foil	No	**Working temperature**	-5 ÷ 60 °C	**Cover model**	Loose
Suitable for circuit integrity	No	**Number of permanent partitions**	2	**Number of plug-in partitions**	0
With cable fixing clip	No	**With duct connector**	No	**Delivery on roll**	No
Pre-stamping	No				

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Instruction booklet

Istruzioni minicanali.pdf



Certification

Canali e Minic Serie MC-CP.pdf



Certification

LICENCE 669941_CP-MC.pdf

Barcode

8054320287070

Cardboard

60 MT

0.248x0.143x2.03 [m]

22.998 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.