


## ECS25100

# SLOTTED TRUNKING WITH COVER S 4/6/4 DIM. 25X100





### Technical Symbols/Marks/Approvals

UL94	GWT	CC	
V0	960°	6	





#### **Norms**

EN 50085-1 EN 50085-2-3 UL 1565

## **Description**

Slotted trunking made of self-extinguishing PVC-based technopolymer (UL94 - V0). Perforated bottom according to the Standard DIN 43659. Second break line at the base of the slots permits to remove the whole trunking wall (with tool).

#### **Etim**

# GROUP EG000007 - Slotted cable trunking system CLASS EC000012 - Slotted cable trunking system

NE EC REPRESENTATIVI

Material	Polyvinyl chloride (PVC)	Halogen free	No	Colour	Grey
Type of fastening	Bottom perforation	Width	25 mm	Height	100 mm
Length	2 m	Distance of slots	6 mm	Slit width	4 mm
Type of side wall	Hole-/slot punching	Self-extinguishing	Yes	Flexible	No
Usable cross section	2156 mm <sup>2</sup>	With cover	Yes	RAL-number	7030

#### **Technical Characteristics**

Separator predisposition NC





### **Barcode**



8050507874743

Cardboard

20 MT

11 [kg]



8054320280545

Pallet

800 MT

440 [kg]