



IMMAGINE
RAPPRESENTATIVA  REPRESENTATIVE
IMAGE

ECS25100

SLOTTED TRUNKING WITH COVER S 4/6/4 DIM. 25X100



Trunkings > Panelboards systems > Cable management >
Slotted trunkings > Slotted cable trunking > Grey - type s -
narrow slots 4/6/4

Technical Symbols/Marks/Approvals



Norms

EN 50085-1 EN 50085-2-3 UL 1565

Description

Slotted trunking made of self-extinguishing PVC-based technopolymer (UL94 - V0). Perforated bottom according to the Standard DIN 43659. Second break line at the base of the slots permits to remove the whole trunking wall (with tool).

Etim

GROUP EG000007 - Slotted cable trunking system

CLASS EC000012 - Slotted cable trunking system

Material	Polyvinyl chloride (PVC)	Halogen free	No	Colour	Grey
Type of fastening	Bottom perforation	Width	25 mm	Height	100 mm
Length	2 m	Distance of slots	6 mm	Slit width	4 mm
Type of side wall	Hole-slot punching	Self-extinguishing	Yes	Flexible	No
Usable cross section	2156 mm ²	With cover	Yes	RAL-number	7030

Technical Characteristics

Separator predisposition NO

Barcode



8050507874743

Cardboard

20 MT

11 [kg]



8054320280545

Pallet

800 MT

440 [kg]