


ECS8040



**SLOTTED TRUNKING WITH COVER S
4/6/4 DIM. 80X40**



Trunkings > Panelboards systems > Cable management > Slotted trunkings > Slotted cable trunking > Grey - type s - narrow slots 4/6/4

IMMAGINE RAPPRESENTATIVA **EC** REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals



Norms

EN 50085-1 EN 50085-2-3 UL 1565

Description

Slotted trunking made of self-extinguishing PVC-based technopolymer (UL94 - V0). Perforated bottom according to the Standard DIN 43659. Second break line at the base of the slots permits to remove the whole trunking wall (with tool).

Etim

GROUP EG000007 - Slotted cable trunking system

CLASS EC000012 - Slotted cable trunking system

Material	Polyvinyl chloride (PVC)	Halogen free	No	Colour	Grey
Type of fastening	Bottom perforation	Width	80 mm	Height	40 mm
Length	2 m	Distance of slots	6 mm	Slit width	4 mm
Type of side wall	Hole-/slot punching	Self-extinguishing	Yes	Flexible	No
Usable cross section	2530 mm ²	With cover	Yes	RAL-number	7030

Technical Characteristics

Separator predisposition SI (2)

Documentation available for download



Certification
Certificato UL A-S
ATL AMF
E331386.pdf



Certification
RINA
DCMTVL_1005538
_380865962_2025.
PDF




Certification
Canali asolati tipo S
IMQ_EI617_2020.p
df

Barcode



8054320286363
Cardboard
40 MT
0.26x0.18x2.027 [m]
24 [kg]



8054320280774
Pallet
720 MT
432 [kg]