

**ECSH10080**



**HALOGEN FREE SLOTTED TRUNKING WITH COVER 4/6/4 DIM. 100X80**

Trunkings > Panelboards systems > Cable management > Slotted trunkings halogen free > Slotted cable trunking > Light grey - type s - narrow slots 4/6/4



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

**Technical Symbols/Marks/Approvals**

HF	UL94 V2	GWT 960°	-25°	+90°	CE	RoHS II	MADE IN ITALY
----	---------	----------	------	------	----	---------	---------------

**Norms**

- EN 50267-2-1   EN 50267-2-2   IEC 60754-1   IEC 60754-2   EN 50085-1
- EN 50085-2-3   UL 1565

**Description**

Slotted trunking made of halogen free tecnopolymer. Self-extinguishing according to the Standard UL94 - V2 at 1,6 mm. Resistance to abnormal heat: up to 960°C (GWT). Dimensione stability between -25°C and +90°C. FPerforated bottom according to the Standard DIN 43659. Second break line at the base of the slots permits to remove the whole trunking wall (with tool).


**Etim**

**GROUP EG000007 - Slotted cable trunking system**

**CLASS EC000012 - Slotted cable trunking system**

<b>Material</b>	Other	<b>Halogen free</b>	Yes	<b>Colour</b>	Grey
<b>Type of fastening</b>	Bottom perforation	<b>Width</b>	100 mm	<b>Height</b>	80 mm
<b>Length</b>	2 m	<b>Distance of slots</b>	6 mm	<b>Slit width</b>	4 mm
<b>Type of side wall</b>	Hole-/slot punching	<b>Self-extinguishing</b>	Yes	<b>Flexible</b>	No
<b>Usable cross section</b>	7156 mm <sup>2</sup>	<b>With cover</b>	Yes	<b>RAL-number</b>	7035

## Documentation available for download



**Certification**  
Canali tipo SH-AH -  
Analysis Test  
Report.pdf

## Barcode



8054320286295  
**Cardboard**  
24 MT  
0.26x0.26x2.03 [m]  
15.4992 [kg]



8055035960517  
**Pallet**  
288 MT  
1.2x0.8x2.2 [m]  
185.9904 [kg]