

ECSH4060



HALOGEN FREE SLOTTED TRUNKING WITH COVER 4/6/4 DIM. 40X60

Trunkings > Panelboards systems > Cable management > Slotted trunkings halogen free > Slotted cable trunking > Light grey - type s - narrow slots 4/6/4



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals

| | | | | | | | |
|----|---------|----------|------|------|----|---------|---------------|
| HF | UL94 V2 | GWT 960° | -25° | +90° | CE | RoHS II | MADE IN ITALY |
|----|---------|----------|------|------|----|---------|---------------|

Norms

- EN 50267-2-1 EN 50267-2-2 IEC 60754-1 IEC 60754-2 EN 50085-1
- EN 50085-2-3 UL 1565

Description

Slotted trunking made of halogen free tecnopolymer. Self-extinguishing according to the Standard UL94 - V2 at 1,6 mm. Resistance to abnormal heat: up to 960°C (GWT). Dimensione stability between -25°C and +90°C. FPerforated bottom according to the Standard DIN 43659. Second break line at the base of the slots permits to remove the whole trunking wall (with tool).


Etim

GROUP EG000007 - Slotted cable trunking system

CLASS EC000012 - Slotted cable trunking system

| | | | | | |
|-----------------------------|----------------------|---------------------------|-------|-------------------|-------|
| Material | Other | Halogen free | Yes | Colour | Grey |
| Type of fastening | Bottom perforation | Width | 40 mm | Height | 60 mm |
| Length | 2 m | Distance of slots | 6 mm | Slit width | 4 mm |
| Type of side wall | Hole-/slot punching | Self-extinguishing | Yes | Flexible | No |
| Usable cross section | 1950 mm ² | With cover | Yes | RAL-number | 7035 |

Documentation available for download



Certification

Canali tipo SH-AH -
Analysis Test
Report.pdf

Barcode



8054320286219

Cardboard

56 MT

0.26x0.18x2.027 [m]

15.68 [kg]



8055035960593

Pallet

1008 MT

1.2x0.8x2.2 [m]

282.24 [kg]