

ECSH8080

**HALOGEN FREE SLOTTED TRUNKING WITH COVER
4/6/4 DIM. 80X80**



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

Trunkings > Panelboards systems > Cable management > Slotted trunkings halogen free > Slotted cable trunking > Light grey - type s - narrow slots 4/6/4

Technical Symbols/Marks/Approvals

HF	UL94 V2	GWT 960°	-25°	+90°	CE	RoHS II	MADE IN ITALY
----	------------	-------------	------	------	----	---------	---------------

Norms

EN 50267-2-1	EN 50267-2-2	IEC 60754-1	IEC 60754-2	EN 50085-1
EN 50085-2-3	UL 1565			

Description

Slotted trunking made of halogen free tecnopolymer. Self-extinguishing according to the Standard UL94 - V2 at 1,6 mm. Resistance to abnormal heat: up to 960°C (GWT). Dimensione stability between -25°C and +90°C. FPerforated bottom according to the Standard DIN 43659. Second break line at the base of the slots permits to remove the whole trunking wall (with tool).


Etim

GROUP EG000007 - Slotted cable trunking system

CLASS EC000012 - Slotted cable trunking system

Material	Other	Halogen free	Yes	Colour	Grey
Type of fastening	Bottom perforation	Width	80 mm	Height	80 mm
Length	2 m	Distance of slots	6 mm	Slit width	4 mm
Type of side wall	Hole-/slot punching	Self-extinguishing	Yes	Flexible	No
Usable cross section	5620 mm ²	With cover	Yes	RAL-number	7035

Documentation available for download



Certification

Canali tipo SH-AH - Analysis Test Report.pdf

Barcode



8054320286141

Cardboard

30 MT

0.26x0.26x2.03 [m]

16.5 [kg]



8055035960661

Pallet

360 MT

1.2x0.8x2.2 [m]

198 [kg]