

**ECSH8080**

**HALOGEN FREE SLOTTED TRUNKING WITH COVER  
4/6/4 DIM. 80X80**



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

Trunkings > Panelboards systems > Cable management > Slotted trunkings halogen free > Slotted cable trunking > Light grey - type s - narrow slots 4/6/4

**Technical Symbols/Marks/Approvals**

HF	UL94 V2	GWT 960°	-25°	+90°	CE	RoHS II	MADE IN ITALY
----	------------	-------------	------	------	----	---------	---------------

**Norms**

EN 50267-2-1	EN 50267-2-2	IEC 60754-1	IEC 60754-2	EN 50085-1
EN 50085-2-3	UL 1565			

**Description**

Slotted trunking made of halogen free tecnopolymer. Self-extinguishing according to the Standard UL94 - V2 at 1,6 mm. Resistance to abnormal heat: up to 960°C (GWT). Dimensione stability between -25°C and +90°C. FPerforated bottom according to the Standard DIN 43659. Second break line at the base of the slots permits to remove the whole trunking wall (with tool).


**Etim**

**GROUP EG000007 - Slotted cable trunking system**

**CLASS EC000012 - Slotted cable trunking system**

<b>Material</b>	Other	<b>Halogen free</b>	Yes	<b>Colour</b>	Grey
<b>Type of fastening</b>	Bottom perforation	<b>Width</b>	80 mm	<b>Height</b>	80 mm
<b>Length</b>	2 m	<b>Distance of slots</b>	6 mm	<b>Slit width</b>	4 mm
<b>Type of side wall</b>	Hole-/slot punching	<b>Self-extinguishing</b>	Yes	<b>Flexible</b>	No
<b>Usable cross section</b>	5620 mm <sup>2</sup>	<b>With cover</b>	Yes	<b>RAL-number</b>	7035

**Documentation available for download**



**Certification**

Canali tipo SH-AH - Analysis Test Report.pdf

## Barcode



8054320286141

**Cardboard**

30 MT

0.26x0.26x2.03 [m]

16.5 [kg]



8055035960661

**Pallet**

360 MT

1.2x0.8x2.2 [m]

198 [kg]