elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECSSB3

SEPARATION AND DERIVATION BOX 250X250X100 mm

Trunkings > Wall and ceiling > Solid cable trunkings > Series cp - fittings > Junction box for cable trunkings

Technical Symbols/Marks/Approvals

IK07 | IP40 | GWT 650° | CE | RoHS II | MADE IN ITALY

Norms

EN 50085-1 EN50085-2-1

Description

Separation box for multi-compartment ducts. Used to separate various circuits and make branches of the same and/or different sizes.

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002600 - Box/housing for surface mounting on the wall/ceiling

Rated insulation voltage Ui	400 V	**Mounting method**	Wall-/ceiling mounting	**Degree of protection (IP)**	IP40
Material	Plastic	**Halogen free**	Yes	**Surface protection**	Untreated
Colour	White	**Width**	250 mm	**Depth**	100 mm
Model	Junction box	**Length**	250 mm	**Working temperature**	-5 ÷ 60 °C
Explosion-tested version	No	**For Ex-zone gas**	None	**For Ex-zone dust**	None
Cover model	Blind cover	**Circuit integrity**	None	**Equipped with**	None
Shape	Square	**Number of inlets**	4	**Inlet from the rear**	No
Transparent cover	No	**Connectable**	No	**Mounting in the soil**	No
Mounting under water	No	**Type of housing feed-through**	Trimmable step membrane	**Cover attachment**	Screwed
Castable	No	**Casting compound included**	No	**Sealable**	No
With screening	No	**Weatherproof**	No		

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Certification

Canali CPH IMQ_CA02.06517_2020.pdf



Certification

Canali e Minic Serie MC-CP.pdf

Barcode

barcode

8032636769060

Unit

1 NR

1.25 [kg]

8033576778624

Cardboard

4 NR

0.39x0.295x0.3 [m]

5 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.