

ECTC1525BL

**PLIABLE PVC CONDUIT 33212 Ø25 mm
- 50 m - BLUE**



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

Conduits and fittings > Conduits > Corrugated conduits > Series tc15 - pvc - class 33212 - 750 n > plastic conduits > White

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-22


Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	Material	Polyvinyl chloride (PVC)	Halogen free	No
Colour	Blue	RAL-number	5005	UV resistant	No
Suitable for underground installation	No	Operating temperature	-5-60 °C	Bending strength	Pliable
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	Impact strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	With sleeve	No
Fire retardant version	Yes	Surface mounting	No	Suitable for installation on wood	No
Suitable for hollow wall installation	No	Suitable for concrete installation	No	Machine and systems installation	No
Suitable for underfloor installation (screed)	No	Suitable for outdoor installation	No	Inner diameter	17.7 mm
Outer diameter	25 mm	High conducting inner coating	No	With metre indication	No

Documentation available for download



Certification

Tubo corrugato
IMQ_EN836_2023
AV.pdf

Barcode



8054320285564

Cardboard

50 MT

0.6x0.6x0.16 [m]

3.9 [kg]



8057711598052

Pallet

3000 MT

0.8x1.2x2.5 [m]

234 [kg]