

## ECTC1532TVE

### PLIABLE PVC CONDUIT 33212 Ø32 mm - 25 m WITH DRAW TAPE - GREEN



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

Conduits and fittings > Conduits > Corrugated conduits > Series tc15 - pvc - class 33212 - 750 n > plastic conduits > White - cable puller

#### Technical Symbols/Marks/Approvals



#### Norms

EN 61386-1 EN 61386-22

## Etim

### GROUP EG000002 - Pipes/hoses for cable installation


### CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	Material	Polyvinyl chloride (PVC)	Halogen free	No
Colour	Green	RAL-number	6029	UV resistant	No
Suitable for underground installation	No	Operating temperature	-5-60 °C	Bending strength	Pliable
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	Impact strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	With sleeve	No
Fire retardant version	Yes	Surface mounting	No	Suitable for installation on wood	No
Suitable for hollow wall installation	No	Suitable for concrete installation	No	Machine and systems installation	No
Suitable for underfloor installation (screed)	No	Suitable for outdoor installation	No	Inner diameter	23.5 mm
Outer diameter	32 mm	High conducting inner coating	No	With metre indication	No

## Technical Characteristics

Lunghezza Bobina 25 m

## Documentation available for download



## Barcode




8054320285397

### Cardboard

25 MT

0.5x0.5x0.15 [m]

3.235 [kg]



8057711598229

### Pallet

1600 MT

0.8x1.2x2.5 [m]

207.04 [kg]