

ECTC182010

PLIABLE PVC CONDUIT 33412 Ø20 mm - 10 m

Conduits and fittings > Conduits > Corrugated conduits >
Series tc18 - pvc -25°C - class 33412 - 750 n > plastic conduits
> Grey - 10 meters-roll



Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-22


Etim

GROUP EG000002 - Pipes/hoses for cable installation


CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	Material	Polyvinyl chloride (PVC)	Halogen free	No
Colour	Grey	RAL-number	7031	UV resistant	No
Suitable for underground installation	No	Operating temperature	-25-60 °C	Bending strength	Pliable
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	Impact strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	With sleeve	No
Fire retardant version	Yes	Surface mounting	No	Suitable for installation on wood	No
Suitable for hollow wall installation	No	Suitable for concrete installation	Yes	Machine and systems installation	No
Suitable for underfloor installation (screed)	No	Suitable for outdoor installation	No	Inner diameter	13.4 mm
Outer diameter	20 mm	High conducting inner coating	No	With metre indication	No

Documentation available for download



Barcode



8032793879466

Unit

1 NR

0.6994 [kg]



8033576778952

Pallet

216 NR

151.0704 [kg]