

ECTG1240B-2

RIGID CONDUIT 22211 Ø40 mm - 2 m - BELL END



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Conduits and fittings > Conduits > Rigid conduits > Series tg12
- pvc - class 22211 - 320 n > plastic conduits > 2 meters -
length - bell end

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-21


Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	Material	Polyvinyl chloride (PVC)	Halogen free	No
Colour	Grey	RAL-number	7035	UV resistant	Yes
Suitable for underground installation	No	Operating temperature	-5-60 °C	Bending strength	Rigid
Compressive strength class according to EN 61386-1	Light (class 2 / 1 Joule)	Impact strength class according to EN 61386-1	Light (class 2 / 1 Joule)	With sleeve	Yes
Fire retardant version	Yes	Surface mounting	Yes	Suitable for installation on wood	Yes
Suitable for hollow wall installation	Yes	Suitable for concrete installation	No	Machine and systems installation	No
Suitable for underfloor installation (screed)	No	Suitable for outdoor installation	No	Inner diameter	36.8 mm
Outer diameter	40 mm	High conducting inner coating	No	With metre indication	No

Documentation available for download



Barcode



8054320284932

Cardboard

20 MT

5.934 [kg]



8057711598687

Pallet

360 MT

106.812 [kg]