

## ECTG1250

### RIGID CONDUIT 22211 Ø50 mm - 3 m - BUNDLE 15

Conduits and fittings > Conduits > Rigid conduits > Series tg12 - pvc - class 22211 - 320 n > plastic conduits > 3 meters - lenght



IMMAGINE RAPPRESENTATIVA  REPRESENTATIVE IMAGE

#### Technical Symbols/Marks/Approvals



#### Norms

EN 61386-1 EN 61386-21

## Description

Rigid protective conduit made of impact-resistant PVC-based technopolymer. Flame propagation resistance: self-extinguishing in less than 30". Resistance to abnormal heat: up to 960°C (GWT IEC 60695-2-11 standard). UV resistant. Compression resistance 320 N. Insulation resistance 100 MΩ at 500 V for 1 minute. Dielectric strength 2000 V at 50 Hz for 15 minutes. Classification: light -22212 according to EN 61386-1, EN 61386-22 standards. Nominal outside diameter 50 mm

## Etim

**GROUP EG000002 - Pipes/hoses for cable installation**

**CLASS EC001174 - Plastic installation tube**

<b>Flush-mounted installation</b>	Yes	<b>Material</b>	Polyvinyl chloride (PVC)	<b>Halogen free</b>	No
<b>Colour</b>	Grey	<b>RAL-number</b>	7035	<b>UV resistant</b>	Yes
<b>Suitable for underground installation</b>	No	<b>Operating temperature</b>	-5-60 °C	<b>Bending strength</b>	Rigid
<b>Compressive strength class according to EN 61386-1</b>	Light (class 2 / 1 Joule)	<b>Impact strength class according to EN 61386-1</b>	Light (class 2 / 1 Joule)	<b>With sleeve</b>	No
<b>Fire retardant version</b>	Yes	<b>Surface mounting</b>	Yes	<b>Suitable for installation on wood</b>	Yes
<b>Suitable for hollow wall installation</b>	Yes	<b>Suitable for concrete installation</b>	No	<b>Machine and systems installation</b>	No
<b>Suitable for underfloor installation (screed)</b>	No	<b>Suitable for outdoor installation</b>	No	<b>Inner diameter</b>	46.4 mm
<b>Outer diameter</b>	50 mm	<b>High conducting inner coating</b>	No	<b>With metre indication</b>	No

## Technical Characteristics

**Lunghezza Barra** 3 m

## Barcode




8054320284925

**Cardboard**

15 MT

5.6205 [kg]



8057711598694

**Pallet**

360 MT

134.892 [kg]