

## ECTG1516

### RIGID CONDUIT 33211 Ø16 mm - 3 m - BUNDLE 102

Conduits and fittings > Conduits > Rigid conduits > Series tg15 - pvc - class 33211 - 750 n > plastic conduits > 3 meters - lenght



#### Technical Symbols/Marks/Approvals



#### Norms

EN 61386-1 EN 61386-21

## Description

Rigid protective conduit made of impact-resistant PVC-based technopolymer. Flame propagation resistance: self-extinguishing in less than 30". Resistance to abnormal heat: up to 960°C (GWT IEC 60695-2-11 standard). UV resistant. Compression resistance 750 N. Insulation resistance 100 MΩ at 500 V for 1 minute. Dielectric strength 2000 V at 50 Hz for 15 minutes. Classification: medium -33211 according to EN 61386-1, EN 61386-22 standards. Nominal outside diameter 16 mm

## Etim

**GROUP EG000002 - Pipes/hoses for cable installation**


**CLASS EC001174 - Plastic installation tube**

|   |                            |  |                            |  |         |
|---|----------------------------|--|----------------------------|--|---------|
| <b>Flush-mounted installation</b>                         | Yes                        | <b>Material</b>                                      | Polyvinyl chloride (PVC)   | <b>Halogen free</b>                      | No      |
| <b>Colour</b>   | Grey                       | <b>RAL-number</b>                                    | 7035                       | <b>UV resistant</b>                      | Yes     |
| <b>Suitable for underground installation</b>              | Yes                        | <b>Operating temperature</b>                         | -5-60 °C                   | <b>Bending strength</b>                  | Rigid   |
| <b>Compressive strength class according to EN 61386-1</b> | Medium (class 3 / 2 Joule) | <b>Impact strength class according to EN 61386-1</b> | Medium (class 3 / 2 Joule) | <b>With sleeve</b>                       | No      |
| <b>Fire retardant version</b>                             | Yes                        | <b>Surface mounting</b>                              | Yes                        | <b>Suitable for installation on wood</b> | Yes     |
| <b>Suitable for hollow wall installation</b>              | Yes                        | <b>Suitable for concrete installation</b>            | Yes                        | <b>Machine and systems installation</b>  | Yes     |
| <b>Suitable for underfloor installation (screed)</b>      | Yes                        | <b>Suitable for outdoor installation</b>             | Yes                        | <b>Inner diameter</b>                    | 13.3 mm |
| <b>Outer diameter</b>                                     | 16 mm                      | <b>High conducting inner coating</b>                 | No                         | <b>With metre indication</b>             | No      |


## Technical Characteristics

**Lunghezza Barra** 3 m


### Documentation available for download



**Certification**  
Tubo Rigido TG15  
e  
Raccordi\_2023.pdf




**Certification**  
Tubo rigido  
IMQ\_EN835\_2023-  
01-12.pdf




**Certification**  
LICENCE NF -  
TG15 -2022 -  
Licence - Certificat  
Produits-14694838-  
778138-  
0000732340-  
6.p....pdf

### Barcode



8054320284888  
**Cardboard**  
102 MT  
8.6394 [kg]



barcode  
8057711598731  
**Pallet**  
3162 MT  
3x0.61x0.62 [m]  
267.8214 [kg]