


ECTG1516-2

RIGID CONDUIT 33211 Ø16 mm - 2 m - BUNDLE 68

Conduits and fittings > Conduits > Rigid conduits > Series tg15 - pvc - class 33211 - 750 n > plastic conduits > 2 meters - lenght



Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-21

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	Material	Polyvinyl chloride (PVC)	Halogen free	No
Colour	Grey	RAL-number	7035	UV resistant	Yes
Suitable for underground installation	Yes	Operating temperature	-5-60 °C	Bending strength	Rigid
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	Impact strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	With sleeve	No
Fire retardant version	Yes	Surface mounting	Yes	Suitable for installation on wood	Yes
Suitable for hollow wall installation	Yes	Suitable for concrete installation	No	Machine and systems installation	Yes
Suitable for underfloor installation (screed)	Yes	Suitable for outdoor installation	Yes	Inner diameter	13.3 mm
Outer diameter	16 mm	High conducting inner coating	No	With metre indication	No

Documentation available for download

Certification
Tubo Rigido TG15 e Raccordi_2023.pdf

Certification
Tubo rigido IMQ_EN835_2023-01-12.pdf

Certification
LICENCE NF - TG15 -2022 - Licence - Certificat Produits-14694838-778138-0000732340-6.p....pdf

Barcode



8054320284871

Cardboard

68 MT

5.9228 [kg]



8057711598748

Pallet

2108 MT

2x0.61x0.605 [m]

183.6068 [kg]