

ECTG1516B



RIGID CONDUIT 33211 Ø16 mm - 3 m - BELL END

Conduits and fittings > Conduits > Rigid conduits > Series tg15
- pvc - class 33211 - 750 n > plastic conduits > 3 meters -
length - bell end



Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-21

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	Material	Polyvinyl chloride (PVC)	Halogen free	No
Colour	Grey	RAL-number	7035	UV resistant	Yes
Suitable for underground installation	Yes	Operating temperature	-5-60 °C	Bending strength	Rigid
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	Impact strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	With sleeve	Yes
Fire retardant version	Yes	Surface mounting	Yes	Suitable for installation on wood	Yes
Suitable for hollow wall installation	Yes	Suitable for concrete installation	No	Machine and systems installation	Yes
Suitable for underfloor installation (screed)	Yes	Suitable for outdoor installation	Yes	Inner diameter	13.3 mm
Outer diameter	16 mm	High conducting inner coating	No	With metre indication	No

Documentation available for download



Certification

LICENCE NF -
TG15 -2022 -
Licence - Certificat
Produits-14694838-
778138-
0000732340-
6.p....pdf

Barcode



8054320284864

Cardboard

75 MT

7.35 [kg]



8057711598755

Pallet

4500 MT

3x0.61x0.62 [m]

441 [kg]