

ECTG1525

RIGID CONDUIT 33211 Ø25 mm - 3 m

Conduits and fittings > Conduits > Rigid conduits > Series tg15 - pvc - class 33211 - 750 n > plastic conduits > 3 meters - lenght



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-21

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	Material	Polyvinyl chloride (PVC)	Halogen free	No
Colour	Grey	RAL-number	7035	UV resistant	Yes
Suitable for underground installation	Yes	Operating temperature	-5-60 °C	Bending strength	Rigid
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	Impact strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	With sleeve	No
Fire retardant version	Yes	Surface mounting	Yes	Suitable for installation on wood	Yes
Suitable for hollow wall installation	Yes	Suitable for concrete installation	Yes	Machine and systems installation	Yes
Suitable for underfloor installation (screed)	Yes	Suitable for outdoor installation	Yes	Inner diameter	21.7 mm
Outer diameter	25 mm	High conducting inner coating	No	With metre indication	No

Technical Characteristics

Lunghezza Barra 3 m

Documentation available for download



Certification
Tubo Rigido TG15
e
Raccordi_2023.pdf



Certification
Tubo rigido
IMQ_EN835_2023-
01-12.pdf



Certification
LICENCE NF -
TG15 -2022 -
Licence - Certificat
Produits-14694838-
778138-
0000732340-
6.p....pdf

Barcode



8054320284802
Cardboard
60 MT
9.804 [kg]



barcode
8057711598816
Pallet
1440 MT
3x0.61x0.62 [m]
235.296 [kg]