

## ECTG1525B-2

### RIGID CONDUIT 33211 Ø25 mm - 2 m - BELL END



Conduits and fittings > Conduits > Rigid conduits > Series tg15  
- pvc - class 33211 - 750 n > plastic conduits > 2 meters -  
length - bell end



IMMAGINE  
RAPPRESENTATIVA

EC  
REPRESENTATIVE  
IMAGE

#### Technical Symbols/Marks/Approvals



#### Norms

EN 61386-1 EN 61386-21

## Etim

### GROUP EG000002 - Pipes/hoses for cable installation

#### CLASS EC001174 - Plastic installation tube

|                                                    |                            |                                               |                            |                                   |         |
|----------------------------------------------------|----------------------------|-----------------------------------------------|----------------------------|-----------------------------------|---------|
| Flush-mounted installation                         | Yes                        | Material                                      | Polyvinyl chloride (PVC)   | Halogen free                      | No      |
| Colour                                             | Grey                       | RAL-number                                    | 7035                       | UV resistant                      | Yes     |
| Suitable for underground installation              | Yes                        | Operating temperature                         | -5-60 °C                   | Bending strength                  | Rigid   |
| Compressive strength class according to EN 61386-1 | Medium (class 3 / 2 Joule) | Impact strength class according to EN 61386-1 | Medium (class 3 / 2 Joule) | With sleeve                       | Yes     |
| Fire retardant version                             | Yes                        | Surface mounting                              | Yes                        | Suitable for installation on wood | Yes     |
| Suitable for hollow wall installation              | Yes                        | Suitable for concrete installation            | No                         | Machine and systems installation  | Yes     |
| Suitable for underfloor installation (screed)      | Yes                        | Suitable for outdoor installation             | Yes                        | Inner diameter                    | 21.7 mm |
| Outer diameter                                     | 25 mm                      | High conducting inner coating                 | No                         | With metre indication             | No      |

## Documentation available for download



**Certification**

LICENCE NF -  
TG15 -2022 -  
Licence - Certificat  
Produits-14694838-  
778138-  
0000732340-  
6.p....pdf

## Barcode



8054320284772

**Cardboard**

34 MT

6.0452 [kg]

 barcode

8057711598847

**Pallet**

1224 MT

2x0.61x0.605 [m]

217.6272 [kg]