

**ECTG1525CR**

**RIGID CONDUIT S.33211 Ø 25 mm - RED RAL3000 - 3 m**

Enclosures > Special application systems > Emergency line > Conduits and fittings > Plastic conduits



**Technical Symbols/Marks/Approvals**

UL94 V0	GWT 960°	IK07	CE	RoHS II	MADE IN ITALY
------------	-------------	------	----	---------	---------------------

**Norms**

EN 61386-1 EN 61386-21

**Etim**

**GROUP EG000002 - Pipes/hoses for cable installation**

**CLASS EC001174 - Plastic installation tube**

<b>Flush-mounted installation</b>	Yes	<b>Material</b>	Polyvinyl chloride (PVC)	<b>Halogen free</b>	No
<b>Colour</b>	Red	<b>RAL-number</b>	3000	<b>UV resistant</b>	Yes
<b>Suitable for underground installation</b>	Yes	<b>Operating temperature</b>	-5-60 °C	<b>Bending strength</b>	Rigid
<b>Compressive strength class according to EN 61386-1</b>	Medium (class 3 / 2 Joule)	<b>Impact strength class according to EN 61386-1</b>	Medium (class 3 / 2 Joule)	<b>With sleeve</b>	Yes
<b>Fire retardant version</b>	Yes	<b>Surface mounting</b>	Yes	<b>Suitable for installation on wood</b>	Yes
<b>Suitable for hollow wall installation</b>	Yes	<b>Suitable for concrete installation</b>	No	<b>Machine and systems installation</b>	Yes
<b>Suitable for underfloor installation (screed)</b>	Yes	<b>Suitable for outdoor installation</b>	Yes	<b>Inner diameter</b>	21.7 mm
<b>Outer diameter</b>	25 mm	<b>High conducting inner coating</b>	No	<b>With metre indication</b>	No

## Barcode



8056351664158

### Cardboard

60 MT

9.804 [kg]



8056351663915

### Pallet

1440 MT

3x0.61x0.62 [m]

235.296 [kg]