

ECTG1540-2

RIGID CONDUIT 33211 Ø40 mm - 2 m - BUNDLE 20

Conduits and fittings > Conduits > Rigid conduits > Series tg15 - pvc - class 33211 - 750 n > plastic conduits > 2 meters - lenght



IMMAGINE RAPPRESENTATIVA  REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-21

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	Material	Polyvinyl chloride (PVC)	Halogen free	No
Colour	Grey	RAL-number	7035	UV resistant	Yes
Suitable for underground installation	Yes	Operating temperature	-5-60 °C	Bending strength	Rigid
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	Impact strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	With sleeve	No
Fire retardant version	Yes	Surface mounting	Yes	Suitable for installation on wood	Yes
Suitable for hollow wall installation	Yes	Suitable for concrete installation	No	Machine and systems installation	Yes
Suitable for underfloor installation (screed)	Yes	Suitable for outdoor installation	Yes	Inner diameter	35.9 mm
Outer diameter	40 mm	High conducting inner coating	No	With metre indication	No

Documentation available for download

Certification

Tubo Rigido TG15 e Raccordi_2023.pdf

Certification

Tubo rigido IMQ_EN835_2023-01-12.pdf

Certification

LICENCE NF - TG15 -2022 - Licence - Certificat Produits-14694838-778138-0000732340-6.p....pdf

Barcode



8054320284710

Cardboard

20 MT

6.634 [kg]



8057711598908

Pallet

360 MT

2x0.61x0.605 [m]

119.412 [kg]