

**ECTG2032B**



**HF RIGID CONDUIT 22431 Ø32 mm - 3 m - BELL END**

Conduits and fittings > Conduits > Rigid conduits > Series tg20  
- pp - class 22431 - 320 n > plastic conduits > 3 meters - lenght  
- bell end



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

**Technical Symbols/Marks/Approvals**

HF	+90°	CE	RoHS II	MADE IN ITALY
----	------	----	---------	---------------

**Norms**

EN 61386-1 EN 61386-21 IEC 60754-1 IEC 60754-2 EN 61034-2

**Etim**

**GROUP EG000002 - Pipes/hoses for cable installation**


**CLASS EC001174 - Plastic installation tube**

<b>Flush-mounted installation</b>	Yes	<b>Material</b>	Polypropylene (PP)	<b>Halogen free</b>	Yes
<b>Colour</b>	Grey	<b>RAL-number</b>	7035	<b>UV resistant</b>	No
<b>Suitable for underground installation</b>	No	<b>Operating temperature</b>	-25-105 °C	<b>Bending strength</b>	Rigid
<b>Compressive strength class according to EN 61386-1</b>	Light (class 2 / 1 Joule)	<b>Impact strength class according to EN 61386-1</b>	Light (class 2 / 1 Joule)	<b>With sleeve</b>	Yes
<b>Fire retardant version</b>	Yes	<b>Surface mounting</b>	Yes	<b>Suitable for installation on wood</b>	Yes
<b>Suitable for hollow wall installation</b>	Yes	<b>Suitable for concrete installation</b>	Yes	<b>Machine and systems installation</b>	Yes
<b>Suitable for underfloor installation (screed)</b>	Yes	<b>Suitable for outdoor installation</b>	Yes	<b>Inner diameter</b>	28.4 mm
<b>Outer diameter</b>	32 mm	<b>High conducting inner coating</b>	No	<b>With metre indication</b>	No

**Technical Characteristics**

**Lunghezza Barra** 3 m

## Documentation available for download




**Certification**  
Test Report Serie  
TG20-TG21  
Halogen Free-pH-  
HCl\_IMQ.pdf

## Barcode



8054320284604  
**Cardboard**  
30 MT  
5.637 [kg]



barcode  
8057711599004  
**Pallet**  
840 MT  
157.836 [kg]