

ECTG2040B

HF RIGID CONDUIT 22431 Ø40 mm - 3 m - BELL END



IMMAGINE RAPPRESENTATIVA  REPRESENTATIVE IMAGE

Conduits and fittings > Conduits > Rigid conduits > Series tg20
- pp - class 22431 - 320 n > plastic conduits > 3 meters - lenght
- bell end

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-21 IEC 60754-1 IEC 60754-2 EN 61034-2

Etim

GROUP EG000002 - Pipes/hoses for cable installation


CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	Material	Polypropylene (PP)	Halogen free	Yes
Colour	Grey	RAL-number	7035	UV resistant	No
Suitable for underground installation	No	Operating temperature	-25-105 °C	Bending strength	Rigid
Compressive strength class according to EN 61386-1	Light (class 2 / 1 Joule)	Impact strength class according to EN 61386-1	Light (class 2 / 1 Joule)	With sleeve	Yes
Fire retardant version	Yes	Surface mounting	Yes	Suitable for installation on wood	Yes
Suitable for hollow wall installation	Yes	Suitable for concrete installation	Yes	Machine and systems installation	Yes
Suitable for underfloor installation (screed)	Yes	Suitable for outdoor installation	Yes	Inner diameter	36.2 mm
Outer diameter	40 mm	High conducting inner coating	No	With metre indication	No

Technical Characteristics


Lunghezza Barra 3 m

Documentation available for download




Certification
Test Report Serie
TG20-TG21
Halogen Free-pH-
HCl_IMQ.pdf

Barcode



8054320284598
Cardboard
30 MT
7.734 [kg]



8057711599011
Pallet
540 MT
139.212 [kg]