

ECTG2150



HF RIGID CONDUIT 33421 Ø50 mm - 3 m



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

Conduits and fittings > Conduits > Rigid conduits > Series tg21 - pp - class 33421 - 750 n > plastic conduits > 3 meters - lenght

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-21 IEC 60754-1 IEC 60754-2 EN 61034-2

Description

Rigid protective conduit made of halogen-free technopolymer according to EN 60754-1, EN 60754-2, EN 60754-3 standards. LSZH (Low Smoke, Zero Halogen) according to EN 61034-1, EN 61034-2. Flame propagation resistance: self-extinguishing in less than 30". Compression resistance 750 N. Minimum operating temperature -25°C. Maximum operating temperature +90°C. Insulation resistance 100 MΩ at 500 V for 1 minute. Dielectric strength 2000 V at 50 Hz for 15 minutes. Classification: medium -33411 according to EN 61386-1, EN 61386-22 standards. Nominal outside diameter 50 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation


CLASS EC001174 - Plastic installation tube

| | | | | | |
|---|----------------------------|--|----------------------------|--|---------|
| Flush-mounted installation | Yes | Material | Polypropylene (PP) | Halogen free | Yes |
| Colour | Grey | RAL-number | 7035 | UV resistant | No |
| Suitable for underground installation | No | Operating temperature | -25-90 °C | Bending strength | Rigid |
| Compressive strength class according to EN 61386-1 | Medium (class 3 / 2 Joule) | Impact strength class according to EN 61386-1 | Medium (class 3 / 2 Joule) | With sleeve | No |
| Fire retardant version | Yes | Surface mounting | Yes | Suitable for installation on wood | Yes |
| Suitable for hollow wall installation | Yes | Suitable for concrete installation | Yes | Machine and systems installation | Yes |
| Suitable for underfloor installation (screed) | Yes | Suitable for outdoor installation | Yes | Inner diameter | 45.2 mm |
| Outer diameter | 50 mm | High conducting inner coating | No | With metre indication | No |

Technical Characteristics


Lunghezza Barra 3 m

Documentation available for download




Certification
Test Report Serie
TG20-TG21
Halogen Free-pH-
HCl_IMQ.pdf

Barcode



8054320284529
Cardboard
15 MT
5.5755 [kg]



8057711599080
Pallet
360 MT
133.812 [kg]