

**ECTP1232**



**HF PLIABLE PP CONDUIT 22323 Ø32 mm - 25 m - ORANGE**

Conduits and fittings > Conduits > Corrugated conduits > Series tp12 - pp - class 22323 - 320 n > plastic conduits > Orange




IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

**Technical Symbols/Marks/Approvals**



**Norms**

EN 61386-1 EN 61386-22 EN 61034-2 EN 50642

**Description**

Flexible corrugated protective conduit made of impact-resistant, self-recovering polypropylene-based technopolymer, halogen-free according to EN 50642:2018/A1:2022 standards. Compression resistance 320 N. Minimum operating temperature -15 °C, maximum +90 °C. Insulation resistance 100 MΩ at 500 V for 1 minute. Dielectric strength 2000 V at 50 Hz for 15 minutes. Classification: light -22323 according to EN 61386-1, EN 61386-22 standards. Micro-hole free. Suitable for liquid concrete. Nominal outside diameter 32 mm

**Etim**

**GROUP EG000002 - Pipes/hoses for cable installation**

**CLASS EC001174 - Plastic installation tube**

<b>Flush-mounted installation</b>	Yes	<b>Material</b>	Polypropylene (PP)	<b>Halogen free</b>	Yes
<b>Colour</b>	Orange	<b>RAL-number</b>	2004	<b>UV resistant</b>	No
<b>Suitable for underground installation</b>	No	<b>Operating temperature</b>	-15-90 °C	<b>Bending strength</b>	Pliable, self recovering
<b>Compressive strength class according to EN 61386-1</b>	Light (class 2 / 1 Joule)	<b>Impact strength class according to EN 61386-1</b>	Light (class 2 / 1 Joule)	<b>With sleeve</b>	No
<b>Fire retardant version</b>	No	<b>Surface mounting</b>	No	<b>Suitable for installation on wood</b>	No
<b>Suitable for hollow wall installation</b>	No	<b>Suitable for concrete installation</b>	No	<b>Machine and systems installation</b>	No
<b>Suitable for underfloor installation (screed)</b>	No	<b>Suitable for outdoor installation</b>	No	<b>Inner diameter</b>	24.7 mm
<b>Outer diameter</b>	32 mm	<b>High conducting inner coating</b>	Yes	<b>With metre indication</b>	No

## Barcode



8054320284444

### Cardboard

25 MT

0.58x0.58x0.16 [m]

2.31 [kg]



8057711599165

### Pallet

1600 MT

0.8x1.2x2.5 [m]

147.84 [kg]