

ECTP2025

HF PAIBLE PP CONDUIT 23323 Ø25 mm - 50 m - BLACK



Conduits and fittings > Conduits > Corrugated conduits > Series tp20 - pp - class 23323 - 750 n > plastic conduits > Black



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-22

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	Material	Polypropylene (PP)	Halogen free	Yes
Colour	Black	RAL-number	9005	UV resistant	No
Suitable for underground installation	No	Operating temperature	-15-90 °C	Bending strength	Pliable, self recovering
Compressive strength class according to EN 61386-1	Light (class 2 / 1 Joule)	Impact strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	With sleeve	No
Fire retardant version	Yes	Surface mounting	Yes	Suitable for installation on wood	Yes
Suitable for hollow wall installation	Yes	Suitable for concrete installation	No	Machine and systems installation	No
Suitable for underfloor installation (screed)	No	Suitable for outdoor installation	No	Inner diameter	18.5 mm
Outer diameter	25 mm	High conducting inner coating	Yes	With metre indication	No

Barcode




8054320284338

Cardboard

50 MT

3.45 [kg]



8057711599271

Pallet

3000 MT

207 [kg]