

**ECTP2032**

**HF PAIBLE PP CONDUIT 23323 Ø32 mm - 50 m - BLACK**



Conduits and fittings > Conduits > Corrugated conduits > Series tp20 - pp - class 23323 - 750 n > plastic conduits > Black



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

**Technical Symbols/Marks/Approvals**



**Norms**

EN 61386-1 EN 61386-22

**Etim**

**GROUP EG000002 - Pipes/hoses for cable installation**

**CLASS EC001174 - Plastic installation tube**

|   |                           |  |                            |  |                          |
|---|---------------------------|--|----------------------------|--|--------------------------|
| <b>Flush-mounted installation</b>                         | Yes                       | <b>Material</b>                                      | Polypropylene (PP)         | <b>Halogen free</b>                      | Yes                      |
| <b>Colour</b>   | Black                     | <b>RAL-number</b>                                    | 9005                       | <b>UV resistant</b>                      | No                       |
| <b>Suitable for underground installation</b>              | No                        | <b>Operating temperature</b>                         | -15-90 °C                  | <b>Bending strength</b>                  | Pliable, self recovering |
| <b>Compressive strength class according to EN 61386-1</b> | Light (class 2 / 1 Joule) | <b>Impact strength class according to EN 61386-1</b> | Medium (class 3 / 2 Joule) | <b>With sleeve</b>                       | No                       |
| <b>Fire retardant version</b>                             | Yes                       | <b>Surface mounting</b>                              | Yes                        | <b>Suitable for installation on wood</b> | Yes                      |
| <b>Suitable for hollow wall installation</b>              | Yes                       | <b>Suitable for concrete installation</b>            | No                         | <b>Machine and systems installation</b>  | No                       |
| <b>Suitable for underfloor installation (screed)</b>      | No                        | <b>Suitable for outdoor installation</b>             | No                         | <b>Inner diameter</b>                    | 24.6 mm                  |
| <b>Outer diameter</b>                                     | 32 mm                     | <b>High conducting inner coating</b>                 | Yes                        | <b>With metre indication</b>             | No                       |

## Barcode




8054320284321

**Cardboard**

25 MT

2.485 [kg]



8057711599288

**Pallet**

1600 MT

159.04 [kg]