
elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



EC20303

VARIABLE INTERNAL ANGLE 130X28 SLATE RAL 7021

Trunkings > Wall and ceiling > Skirting and wall trunkings > Series 20 - trunking fittings > Internal bend for skirting trunkings

Technical Symbols/Marks/Approvals

IP40 | IK08 | GWT 650° | CE | RoHS II | MADE IN ITALY

Norms

EN 50085-1 EN 50085-2-1

Description

Internal angles composed of a flexible inner section, quickly attached with screws, which allows for insulation and continuous separation of cables in their compartments. Rigid cover, adjustable from 70° to 110°, snaps on.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000851 - Inner corner for skirting duct

Degree of protection (IP)	IP40	**Material**	Plastic	**Material quality**	Acrylonitrile butadiene styrene (ABS)
Halogen free	Yes	**Colour**	Anthracite	**Impact strength**	IK08
Height	130 mm	**Depth**	28 mm	**Model**	Base unit and cover
RAL-number	7021	**Sealing lip cover**	None	**Decoration**	None
With carpet border	No	**Angle**	70-110 °		

Documentation available for download



Certification

Battiscopa Serie 20.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8032793876748

Unit

1 NR

0.12 [kg]



8050880881079

Cardboard

5 NR

0.235x0.285x0.105 [m]

0.6 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.