


EC20305



**VARIABLE FLAT ANGLE SLATE 130X28
RAL 7021**

Trunkings > Wall and ceiling > Skirting and wall trunkings > Series 20 - trunking fittings > Flat angle for skirting trunkings



Technical Symbols/Marks/Approvals

IP40	IK08	GWT 650°	CE	RoHS II		MADE IN ITALY
------	------	-------------	----	---------	--	---------------------

Norms

EN 50085-1 EN 50085-2-1

Description

A flat angle that connects two straight sections of duct on the same plane, with an intersection angle ranging from 90° to 170°. It consists of a lower section that can be cut to the required angle, secured to the duct with screws, and a modular upper cover that overlaps the duct. The micro-hooks that secure the duct ensure a tight seal even in the event of significant impacts.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000852 - Flat bend for skirting duct

Degree of protection (IP)	IP40	Material	Plastic	Material quality	Acrylonitrile butadiene styrene (ABS)
Halogen free	Yes	Colour	Anthracite	Impact strength	IK08
Model	Base unit and cover	RAL-number	7021	With protective foil	No
Sealing lip cover	None	Decoration	None	Height baseboard duct	130 mm
Depth plinth skirting duct	28 mm	With carpet border	No		

Documentation available for download

Certification

Battiscopa Serie 20.pdf

General data sheets

SCI_20 BATT.pdf

Barcode



8032793876762

Unit

1 NR

0.18 [kg]



8059307212793

Cardboard

5 NR

0.235x0.285x0.105 [m]

0.9 [kg]