

EC16001

DOUBLE SIDED MODULAR BOXES 2+2 DEVICES WITH 60 mm CENTRE HOLE - GREY



IMMAGINE
RAPPRESENTATIVA

EC

REPRESENTATIVE
IMAGE

Trunkings > Floor cable management > Floor distribution systems > Utility floor boxes > Modular floor box for wiring devices > Floor boxes

Technical Symbols/Marks/Approvals

| | | | | | |
|------|------|-------------|----|---------|---------------------|
| IK07 | IP54 | GWT 650° | CE | RoHS II | MADE IN ITALY |
|------|------|-------------|----|---------|---------------------|

Norms

EN 50085-1 EN 50085-2-4

Description

Double-sided tower made of shock-resistant technopolymer. Designed for 4+4 fixtures with 108.5 mm spacing or for 2+2 fixtures with 60 mm spacing. End cap included for single-sided use. Designed for the entry of 75x17 and 50x12 mm floor trunking. Can be installed on poured or raised floors.

Etim

GROUP EG000005 - Subfloor electrical installation systems

CLASS EC000121 - Surface tank empty


| | | | | | |
|---|--------|--|--------|--|------------|
| Material | Other | Surface protection | Other | Colour | Grey |
| Width | 150 mm | Height | 149 mm | Model | Horizontal |
| Length | 226 mm | RAL-number | 7030 | Number of appliances to build in | 8 |
| Number of units to build in front side | 4 | Number of units to build in rear side | 4 | Suitable for standard switching equipment | Yes |
| Suitable for wet cleaning | Yes | | | | |

Technical Characteristics

| | | | |
|-----------------|----|------------------|--------|
| IP Grade | 54 | wheelbase | 108 mm |
|-----------------|----|------------------|--------|

Documentation available for download

Instruction booklet



Istruzioni_SERIE_1
60_0423.pdf

Barcode



8033576771762

Unit

1 NR

0.16x0.22x0.155 [m]

0.791 [kg]



8059307212441

Cardboard

10 NR

0.4x0.605x0.35 [m]

7.91 [kg]