

**EC16001H**



**HORIZ. EXPANSIONS 2+2 DEVICES WITH 60 mm CENTRE HOLE - GREY**



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

Trunkings > Floor cable management > Floor distribution systems > Utility floor boxes > Modular floor box for wiring devices > Extension sets

**Technical Symbols/Marks/Approvals**

IK07	IP54	GWT 650°	CE	RoHS II	MADE IN ITALY
------	------	----------	----	---------	---------------

**Norms**

EN 50085-1 EN 50085-2-4

**Description**

Horizontal expansion for double-sided tower made of shock-resistant technopolymer. Designed for 4+4 fixtures with 108.5 mm spacing or for 2+2 fixtures with 60 mm spacing. End cap included for single-sided use. Designed for the entry of 75x17 and 50x12 mm floor trunking. Can be installed on poured or raised floors.

**Etim**

**GROUP EG000005 - Subfloor electrical installation systems**

**CLASS EC000121 - Surface tank empty**

<b>Material</b>	Other	<b>Surface protection</b>	Other	<b>Colour</b>	Grey
<b>Width</b>	150 mm	<b>Height</b>	149 mm	<b>Model</b>	Horizontal
<b>Length</b>	176 mm	<b>RAL-number</b>	7030	<b>Number of appliances to build in</b>	8
<b>Number of units to build in front side</b>	4	<b>Number of units to build in rear side</b>	4	<b>Suitable for standard switching equipment</b>	Yes
<b>Suitable for wet cleaning</b>	Yes				

**Technical Characteristics**

<b>IP Grade</b>	54	<b>wheelbase</b>	108 mm
-----------------	----	------------------	--------

## Documentation available for download

### Instruction booklet



Istruzioni\_SERIE\_1  
60\_0423.pdf

## Barcode



8033576771786

### Unit

1 NR

0.2x0.154x0.145 [m]

0.671 [kg]



8059307212458

### Cardboard

10 NR

0.605x0.4x0.35 [m]

6.71 [kg]