elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



EC16002

DOUBLE SIDED MODULAR BOXES 2+2 DEVICES WITH 60 mm CENTRE HOLE - SLATE GREY

Trunkings > Floor cable management > Floor distribution systems > Utility floor boxes > Modular floor box for wiring devices > Floor boxes

Technical Symbols/Marks/Approvals

IP54 | IK07 | GWT 650° | CE | RoHS II | MADE IN ITALY

Norms

EN 50085-1 EN 50085-2-4

Description

Double-sided tower made of shock-resistant technopolymer. Designed for 4+4 fixtures with 108.5 mm spacing or for 2+2 fixtures with 60 mm spacing. End cap included for single-sided use. Designed for the entry of 75x17 and 50x12 mm floor trunking. Can be installed on poured or raised floors.

Etim

GROUP EG000005 - Subfloor electrical installation systems

CLASS EC000121 - Surface tank empty

Material	Other	**Surface protection**	Other	**Colour**	Anthracite
Width	150 mm	**Height**	149 mm	**Model**	Horizontal
Length	226 mm	**RAL-number**	7021	**Number of appliances to build in**	8
Number of units to build in front side	4	**Number of units to build in rear side**	4	**Suitable for standard switching equipment**	Yes
Suitable for wet cleaning	Yes				

Technical Characteristics

IP Grade	54	**wheelbase**	108 mm

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download

Instruction booklet



Istruzioni_SERIE_160_0423.pdf

Barcode

8033576771779
Unit
1 NR
0.2x0.154x0.145 [m]
0.791 [kg]

8059307212472
Cardboard
10 NR
0.605x0.4x0.35 [m]
7.91 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.